

Model Specification for 318i Sedan



Engine

Cylinders/Valves	3/4
Capacity (cc)	1499
Stroke/Bore (mm)	94.6/82
Rated Power/Rated Engine Speed (kW/rpm)	100/4400 - 6000
Max Torque/Engine Speed (Nm/rpm)	220/1250 - 4300
Combined System Torque (Nm)	
Compression Ratio (:1)	10.5
Engine type	B38B15M0

Performance

Top Speed (km/h)	210
Acceleration 0-100km/h (s)	8.9 (M) 9.1 (A)
Standing Start 0-1000m (s)	
Drag Coefficient (c)	0.27 (M) 0.28 (A)
Acceleration 80-120km/h with manual transmission in 5th gear	

Dimensions / weights

Luggage Compartment capacity (l)	480
Ground Clearance (mm)	140
Wheelbase (mm)	2810
Vehicle Length (mm)	4633
Vehicle Width (mm)	1811
Vehicle Height (mm)	1429
Track, Front (mm)	1543
Track, Rear (mm)	1583
Rear overhang	1044
Front disk brakes V=ventilated	16" V
Rear disk brakes V=ventilated	16" V
Turning Circle (m)	11.3

Fuel Consumption




In Town (l/100km)	6.4 (M) 6.2 (A)
Out of Town (l/100km)	4.3
Combined (l/100km)	5.1 (M) 5.0 (A)
CO2 Emissions (g/km)	119 (M) 116 (A)
Tank Capacity (l)	60

Weight

Axle load ratio (unloaded DIN) %	50.9 (M) 50.3 (A)
Unladen (Din Unladen) (kg)	1400 (M) 1425 (A)
Gross Vehicle Mass (GVM) (kg)	1975 (M) 2000 (A)
Permitted Roof Load (kg)	75
Permitted Trailer Load (Braked) (kg)	1300/1500
Permitted Trailer Load (Unbraked) (kg)	695
Permitted Towbar Download (kg)	75
Permitted Axle Load front/rear (kg)	905/1155
Permitted Load (kg)	575
Gross Combination Mass (GCM) (kg)	3350 (M) 3375 (A)
Tare (kg)	1360 (M) 1385 (A)

Wheels

Tyre Dimensions	205/60 R16
Wheel Dimensions	7J x 16
Material	Light Alloy



*The published fuel consumption and CO2 emission figures are established according to legislated technical specifications (UNECE Regulation 101/UN Regulation 83 and SANS 20101 standards), which sets out the procedures that are used to measure the CO2 emissions and fuel consumption. The claimed figures are established using specific tests under standardised, carefully controlled conditions and may differ from consumption achieved under real world conditions with the influences of altitude, road surface, geographic conditions, vehicle options, temperature, humidity, tyres size and driving behaviour amongst others.

EU Unladen mass refers to a vehicle with standard equipment, with 90% fuel tank fill, including a driver (68 kg) and luggage (7 kg). Optional extras and accessories will generally increase this figure.

Please contact your preferred authorized BMW dealer or BMW South Africa (Pty) Ltd. for information on vehicles that are available for sale, and the various specifications and options of vehicles that are available.

Trailer loads may not exceed the load stated for un-braked or for braked trailer and the max tow bar load may not exceed the value stated.

Vehicle heights are measured without the aerial. The heights are slightly higher if measured over the aerial. Measurements are stated for vehicles with standard fittings and may vary when optional equipment is fitted.

The technical data stated refers to the current version of the model selected. Due to certain legal regulations in different countries, deviations in the technical data described here can occur.